



**ELECTRICAL CHARACTERISTICS :**

- 1.D.C.R. : PIN 2-3 = 1 OHM MAX.  
PIN 7-6 = 0.2 OHM MAX.
- 2.INDUCTANCE(@100K HZ , 0.1 Vrms) :  
PIN 2-3 = 100 uH +/- 10%
- 3.LEAKAGE INDUCTANCE(@1M HZ , 0.1Vrms) :  
PIN 2-3 = 700 nH MAX.(7-6 SHORT)
- 4.INTERWINDING CAP(@100K HZ , 0.1Vrms) :  
PIN 2-7 = 25 pF MAX.
- 5.IMPEDANCE(@700K HZ , 0.1Vrms , PIN 7-6 W / H 11 OHM) :  
PIN 2-3 = 100 OHM REF.
- 6.HI-POT(@1875 VAC , 1mA , 2 SEC) : PRI-SEC.
- 7.RoHS COMPLIANT.

						 <b>Atech</b> <sup>®</sup> Atech Technology Co., Ltd. TEL: (02)2794-6667 FAX: (02)2794-8004		TITLE TRANSFORMER	
								DWG NO. ATS-785R	
RELEASE						UNITS	SAFETY		SHEET
NO.	DESCRIPTION	DATE	BY	CHK	APP	DATE	P/N	DRAW	
REVISIONS									