



Technical drawing of a rectangular plate with dimensions and hole specifications. The plate has a total width of 17.01 and a total height of 15.49. The drawing shows a grid of holes with the following specifications:

- Top-left corner: 6 holes of diameter $\phi 1.6$ arranged in a 2x3 grid.
- Top-right corner: 16 holes of diameter $\phi 0.89$ arranged in a 4x4 grid.
- Bottom-left corner: 2 holes of diameter $\phi 3.25$ arranged in a 1x2 grid.
- Bottom-right corner: 8 holes of diameter $\phi 0.89$ arranged in a 2x4 grid.

Key dimensions and positions:

- Top-left corner: 6 holes of diameter $\phi 1.6$ (2x3 grid).
- Top-right corner: 16 holes of diameter $\phi 0.89$ (4x4 grid).
- Bottom-left corner: 2 holes of diameter $\phi 3.25$ (1x2 grid).
- Bottom-right corner: 8 holes of diameter $\phi 0.89$ (2x4 grid).
- Overall dimensions: 17.01 (width) x 15.49 (height).
- Internal dimensions: 11.43 (width of central area), 15.49 (width of central area), 11.43 (height of central area), 5.84 (height of central area), 4.57 (height of central area), 9.14 (height of central area), 6.35 (height of central area), 2.54 (height of central area), 1.27 (width of central area), 2.54 (height of central area).

ELECTRICAL CHARACTERISTICS :

1. VOLTAGE PATING : 125 VAC RMS
2. CURRENT RATING : 1.5 AMP
3. CONTACT RESISTANCE : 20 MILLIOHMS MAX.
4. INSULATION RESISTANCE : 1000 MEGOHMS MIN @500 VDC
5. DIELECTRIC STRENGTH : 1000 VAC RMS 50Hz OR 60Hz, 1MINNUTE
6. RoHS COMPLIANT

								TITLE RJ45 2*1 JACK	
								DWG. NO. RJC-009R	
	RELEASE	03/09/2010	LIGHT	BETTY	KING	UNITS: M/M	SAFETY		SHEET 1 of 1
NO:	DESCRIPTION	DATE	BY	CHK	APPD	DATE 03/09/10	P/N:		DRAW LIGHT
REVISIONS									