



PIN 6.8.10 CUT OFF

ELECTRICAL CHARACTERISTICS :

1. DCR : PIN 1-2 = 35mΩ MAX.  
 PIN 3-4 = 700mΩ MAX.  
 PIN 4-5 = 1000mΩ MAX.  
 PIN 7-9 = 35mΩ MAX.
2. INDUCTANCE (@10KHz, 0.1Vrms) :  
 PIN 3-5 = 764uH ±10%
3. LEAKAGE INDUCTANCE (@100KHz, 0.1Vrms)  
 PIN 3-5 (PIN 1-2, 7-9 SHORT) = 20uH MAX.
4. TURN RATIO (@100KHz, 0.1Vrms) :  
 PIN 3-5 : 2-1 = 8.6 ±2%  
 PIN 3-5 : 7-9 = 9.55 ±2%
5. HI-POT :  
 (@3000VAC, 3mA, 2SEC.) : PIN 3.2- PIN 7
6. RoHS COMPLIANTE

					<b>AOEM.</b>		TITLE: FLYBACK TRANSFORMER	
							DWG. NO. ATS-1396R	
RELEASE					UNITS:	SAFETY		SHEET 1 of 1
NO:	DESCRIPTION	DATE	BY	CHK	APPD	DATE	P/N:	DRAW
REVISIONS								