



ELECTRICAL CHARACTERISTICS :

1. DCR : PIN 1-2 = 110mΩ MAX. , PIN 3-4 = 110mΩ MAX.
PIN 5-6 = 150mΩ MAX. , PIN 7-8 = 200mΩ MAX.
2. INDUCTANCE (@10KHz, 100mVrms) :
PIN 1-4 (PIN 2-3 SHORT) = 48uH MIN.
3. LEAKAGE INDUCTANCE (@200KHz, 0.1Vrms) :
PIN 1-4 (PIN 2.3 SHORT, PIN 5.6.7.8 SHORT) = 150nH MAX.
4. INTERWINDING CAPACITANCE (@100KHz, 0.1Vrms) :
PIN 1-8 (PIN 2-3, PIN 6-7 SHORT) = 6pF MAX.
5. TURN RATIO (@100KHz, 0.1Vrms) :
PIN 1-4 (PIN 2-3 SHORT) : 6-5 = 1.5 ±2%
PIN 1-4 (PIN 2-3 SHORT) : 8-7 = 1 ±2%
6. HI-POT (@600VAC, 5mA, 1SEC) :
PIN 1 (PIN 2-3 SHORT) - PIN 8 (PIN 6-7 SHORT)
7. RoHS COMPLIANTE

							TITLE TRANSFORMER	
							DWG. NO. PL-041R	
RELEASE					UNITES:		SAFETY	
NO: DESCRIPTION					DATE		P/N:	
DATE					BY		DRAW	
CHK					APPD		SHEET 1 of 1	
REVISIONS								