



Open Frame A1652FH-240054(001)

Features

- High Efficiency
- High Reliability
- Application: Telecom, LCD TV, IT

Characteristics

Output Wattage	166W	Load Regulation	±5%
Output Voltage	5Vsb;12V;24V	Ripple & Noise	12V/120mVp-p;5V/150mVp-p;5V WIFI/150mVp-p;3.3V/100mVp-p
Output Current	5Vsb/2.5A;12V/2A;24V/5.4A	Efficiency	82%min@100Vac,max load;86%min@240Vac,max load
Input Voltage	100Vac/240Vac(90~264Vac min/max)	Surge	±1KV,IEC 61000-4-5
Input Current	2.5A(RMS) max	EMI	CISPR 22 class B, FCC class B
Inrush Current	No damage	ESD	Air±8KV, Contact±4KV ,IEC 61000-4-2
Leakage Current(A)	<0.5mA@264Vac	MTBF	100KHrs min.@, 80% load, 25°C (Telcordia SR-332, issue 2)
No Load Power Consumption	<0.5W@264Vac,5Vsb/0.03A		

Environmental

Operating Temperature	0°C ~ +40°C
Storage Temperature	-20°C ~ +85°C
Humidity	20%~90%

Safety

Meet CE

Dimension Diagram Unit:mm

