



#### ELECTRICAL CHARACTERISTICS :

1. IMPEDANCE : 600 ΩHM.
2. DCR : EACH LINE = 12.5 ΩHM MAX.
3. INSERTION LOSS : 1KHZ = 0.5 dB MAX.
4. INSERTION LOSS DISTORTION : 300HZ = ± 1 dB,  
3.4KHZ = ± 1 dB.
5. RETURN LOSS : 300HZ = 14 dB MIN.  
500HZ = 18 dB MIN.  
2KHZ = 18 dB MIN.  
3.4KHZ = 14 dB MIN.
6. ATTENUATION : 30KHZ = 65 dB MIN.  
300KHZ = 65 dB MIN.  
1.1MHZ = 55 dB MIN.

						<b>Atech®</b> Atech Technology Co., Ltd. TEL: (02) 2794-6667 FAX: (02) 2794-8004	TITLE	ADSL SPLITTER MODULE
B	CAN	12/29/2005	BART	MICHAEL	SUEDY		DWG. NO.	ATF074
A	SPEC. & DIM.	03/24/2004	BART	EUGENE	SUEDY	UNITS:	M/M	
	RELEASE	03/19/2004	BART	SIMON	SUEDY	DATE	03/19/04	
NO.	DESCRIPTION	DATE	BY	CHK	APPD	SAFETY	SHEET 1 OF 1	
REVISIONS							DRAW <i>Pair</i>	