



ELECTRICAL CHARACTERISTICS :

(PE-68678,TG74-1505N1 COMPATIBLE)

- DCR : PIN 14-16 = 6-8 = 0.7 OHM MAX.
PIN 1-3 = 0.7 OHM MAX.
PIN 9-11 = 1.0 OHM MAX.
- INDUCTANCE (@100KHZ, 50mV) : PRI. = 1.2mH MIN.
- LEAKAGE INDUCTANCE (@100KHZ, 50mV) : PRI. <SEC. SHORT> = 0.6uH MAX.
- INTERWINDING CAP. (@100KHZ, 50mV) : PRI. - SEC. = 30pF MAX.
- TURNS RATIO : PIN 1-3 : PIN 16-14 = 1CT : 1CT
PIN 6-8 : PIN 11-9 = 1CT : 2CT
- HI-POT (@1500VAC, 1mA, 2SEC) : PRI.-SEC.

						Atech [®]		TITLE T1/E1/ISDN TRANSFORMER	
						Atech Technology Co., Ltd. TEL:022794-6667 FAX:022794-8004		DWG. NO. ATPL-014	
Δ	H = 5.65 MAX.	02/27/2004	BART	AL	SUEDY	UNITS: M/M	SAFETY	SHEET 10F 1	
	RELEASE	07/03/98	PAIR	AL	SUEDY			DRAW <i>Pair</i>	
ND:	DESCRIPTION	DATE	BY	CHK	APPD	DATE			
REVISIONS						02/03/98			