



ELECTRICAL CHARACTERISTICS: (PE-65862 COMPATIBLE)

- D.C.R. : 14-16 = 6-8 = 0.7 OHM MAX. 1-3 = 1.0 OHM MAX.
9-11 = 0.8 OHM MAX.
- INDUCTANCE : ($@100\text{KHZ}, 50\text{mV}$)
PRI. = 1.2mH MIN.
- LEAKAGE INDUCTANCE : ($@100\text{KHZ}, 50\text{mV}$)
PRI. (SEC. SHORT) = 0.6 uH MAX.
- INTERWINDING CAP. : ($@100\text{KHZ}, 50\text{mV}$)
PRI. - SEC. = 30pF MAX.
- TURNS RATIO : PIN 16-14 : PIN 1-3 = 1CT : 2CT
PIN 6-8 : PIN 11-9 = 1 : 1.36CT
- HI-POT : ($@1500\text{ VAC}, 1\text{mA}, 2\text{SEC.}$) PRI. -SEC.

						Atech [®]		TITLE T1/E1/ISDN TRANSFORMER	
						Atech Technology Co., Ltd.		DWG. NO.	
						TEL:(02)2794-6667 FAX:(02)2794-8004		ATPL-037	
RELEASE		12/10/98	PAIR		SUEDY	UNITS:	SAFETY		SHEET 1 OF 1
NO:	DESCRIPTION	DATE	BY	CHK	APP'D	M/M			DRAW
REVISIONS						DATE			Pair
						12/10/98			