



ELECTRICAL CHARACTERISTICS : (FOR PE-64934 COMPATIBLE)

1. ISOLATION : 1500V_{rms} (PRI.-SEC.)
2. TURNS RATIO : PIN 1-2 : 5-6 = 1 : 1 ± 5%
3. PRI. DCL : 1.2mH MIN. @100KHZ 50mV
4. LEAKAGE INDUCTANCE : 0.5 μH MAX. @100KHZ 50mV (SEC. SHORT)
5. D.C.R. : PIN 1-2 = 5-6 = 0.7 OHM MAX.
6. CW/W (PRI.-SEC.) : 25pF MAX.

| | | | | | | | | |
|-----------|-------------|----------------|-------|-----|-------|---|---------------------------------|--------|
| | | | | | | Atech [®] Atech Technology Co. Ltd. TEL:022794-6667 FAX:022794-8004 | TITLE T1/E1/ISDN TRANSFORMER | |
| | | | | | | | UNITS: M/M | SAFETY |
| A | DIMENSION | 12/10 /2001 | DOLLY | AL | SUEDY | DATE | SHEET 1 OF 1 | |
| | RELEASE | 05/20 /99 | PAIR | | SUEDY | DATE | | |
| NO: | DESCRIPTION | DATE | BY | CHK | APPD | DATE | DRAW <i>Pair</i> | |
| REVISIONS | | | | | | 05/20/99 | | |