



ELECTRICAL CHARACTERISTICS:

(FOR MITEL MT8978, MH89780, MT8979, MH89790, MH89791, E1 INTERFACE)

- 1 D.C.R. : PIN 4-8 = 0.1 OHM+/-15% PIN 1-5 = 1.5 OHM+/-15%
PIN 2-6 = 1.5 OHM+/-15%
- 2 INDUCDANCE :(@10KHZ, 0.1Vrms) PIN 4-8 = 400uH +30% , -20%
- 3 IMPEDANCE :(@50KHZ, 0.1Vrms, PIN 4-8 W/H 75 OHM LOAD)
PIN 1-5 = 400 OHM+/-10% PIN 2-6 = 400 OHM+/-10%
- 4 Q VALUE :(@10KHZ, 0.1Vrms) PIN 4-8 = 20 MIN.
- 5 WINDING CAPACITANCE :(@10KHZ, 0.1Vrms,) PIN 1-2 = 85 pF MAX.
PIN 1-4 = 20 pF MAX.
- 6 LEAKAGE :(@10KHZ, 0.1Vrms, W/H PIN 1-2-5-6 SHORT) PIN 4-8
= 450 nH MAX.
- 7 TURN RATIO : PIN 1-5 : 4-8 = 2.5 PIN 2-6 : 4-8 = 2.5
- 8 HI-POT :(@1500 VAC, 1mA 1MINUTE) PRI-SEC-CORE

						Atech [®]		TITLE CEPT OUTPUT TRANSFORMER	
						Atech Technology Co., Ltd.		DWG. NO. ATS-2915T	
						TEL:(02)2794-6667 FAX:(02)2794-8004			
A	CKT	08/12/93	PAIR	SLJEDY	UNITS	SAFETY		SHEET 1 OF 1	
NO:	DESCRIPTION	DATE	BY	CHK	APPD	M/M			DRAW
REVISIONS						08/12/93	E159603	Pair	