



SPECIFICATIONS :

1. INSERTION LOSS (100KHZ-125MHZ) : -1.1dB MAX.
2. RETURN LOSS (100KHZ-60MHZ) : -18dB TYP. (Tx)/-17dB TYP.(Rx)
(60-100 MHZ) : -13dB TYP. (Tx)/-15dB TYP.(Rx)
3. CMRR : (100KHZ-60MHZ) -42dB MIN. (Tx)/-40dB MIN.(Rx)
(60MHZ-100MHZ) -40dB MIN. (Tx)/-35dB MIN.(Rx)
4. CROSSTALK : (100KHZ-60MHZ) -40dB MIN.
(60MHZ-100MHZ) -38dB MIN.
5. RISE TIME (10-90%) : 2.5ns TYP.
6. HI-PDT TEST : 1500 Vrms (INPUT/OUTPUT)

| | | | | | | | | | |
|-----------|-------------|-------|----|-------|--------|-------------------------------------|--|---------------------------------------|------|
| | | | | | | Atech [®] | | TITLE FILTER MODULES 10/100BASE-TX | |
| | | | | | | Atech Technology Co., Ltd. | | DWG. NO. ATF004B | |
| | | | | | | TEL:(02)2794-6667 FAX:(02)2794-8004 | | | |
| RELEASE | 11/27/2001 | DOLLY | AL | SUEDY | UNITS: | SAFETY | | SHEET 1 OF 1 | |
| NO: | DESCRIPTION | DATE | BY | CHK | APPD | M/M | | | DRAW |
| REVISIONS | | | | | | DATE 11/27/01 | | Pair | |