



ELECTRICAL CHARACTERISTICS :

(FOR LXT980/982/983, PE-H1074 COMPATIBLE)

1. D.C.R. : 0.9 OHM MAX. (1/2 PRI. or ELSE WINDING)
2. INDUCTANCE : (@100KHZ, 0.1Vrms, W/H 8mADC) 350uH MIN. (EACH SEC.)
3. LEACKAGE INDUCTANCE : (@100KHZ, 0.1Vrms) 0.5uH MAX. (Rx) ; 1.3uH MAX. (Tx)
4. WINDING CAP. : (@100KHZ, 0.1Vrms) PRI.-SEC. = 30pF TYP.
5. TURNS RATIO : PRI. : SEC. = 2CT : 1CT (TX)
PRI. : SEC. = 1 : 1 (RX)
6. RISE TIME : 2.5ns TYP.
7. CROSSTALK : (@100KHZ - 100MHZ) -38dB MIN.
8. CMRR : (@100KHZ - 100MHZ) -37dB TYP.
9. HI-POT : (@1500 Vrms, 1mA, 2SEC.) PRI. - SEC.

						 Atech [®] Atech Technology Co., Ltd. TEL:022794-6667 FAX:022794-8004	TITLE 10/100 BASE-TX QUAD PORT
B	DIM. / 28.35 MAX.	11/11 /2002	DOLLY	AL	SUEDY		DWG. NO. ATPL-007
A	DIM. / LK	11/24 /00	PAIR		SUEDY	UNITS: M/M SAFETY	
	RELEASE	03/09 /98	PAIR		SUEDY		SHEET 1 OF 1
ND	DESCRIPTION	DATE	BY	CHK	APPD	DATE	DRAW <i>Pair</i>
REVISIONS						03/09/98	