



SPECIFICATIONS : (IR REFLOWABLE 235 ± 5°C)

1. INSERTION LOSS (0.3-100 MHZ) : -1.15dB MAX.
2. RETURN LOSS (0.3-30 MHZ) : -18dB MIN.  
(40 MHZ) : -15.5dB MIN.  
(50 MHZ) : -13dB MIN.  
(60M-80MHZ) : -12dB MIN.
3. CMRR (0.3M-100MHZ) : -40dB MIN.
4. CROSSTALK (0.3M-100MHZ) : -40dB MIN.
5. DCL (@100KHZ, 0.1Vrms, 8mADC) : 350uH MIN.
6. DCR : 0.9 OHM MAX.
7. RISE TIME 2.5 nS TYPICAL
8. HI-PDT TEST : 1500 Vrms.

						<b>Atech®</b> Atech Technology Co., Ltd. TEL:022794-6667 FAX:022794-8004		TITLE 10/100 BASE-T L/P FILTER	
								DWG. NO. ATPL-111A	
RELEASE	08/13/2001	DOLLY		SUEDY	UNITS: M/M	SAFETY		SHEET 1 OF 1	
NO:	DESCRIPTION	DATE	BY	CHK	APPD	DATE	DRAW		Pair
REVISIONS						08/13/01			