



ELECTRICAL CHARACTERISTICS (TLA-6T102 COMPATIBLE)

1. TURN RATIO(±3%) : PIN 16-15-1: 9-10-8 = 1CT : 1
2. PRIMARY OCL INDUCTANCE : 350uH MIN. @ 100KHZ/0.1V WITH 8mA DC BIAS
3. CW/W : 28pF MAX.
4. DCR : 0.9 OHM MAX.
5. INSERTION LOSS(0.3-100MHZ) : -1.0dB MAX.
6. C. M. R.(COMMON TO DIFFERENTIAL) : -45dB MIN. @ 0.3-60 MHZ
-43dB MIN. @ 60-100 MHZ
7. HI-POT ISOLATION : 1500Vrms

TOLERANCES: ±0.25mm

						Atech[®]		TITLE 10/100 BASE-T TRANSFORMER	
						Atech Technology Co., Ltd.		DWG. NO.	
						TEL:(02)2794-6667 FAX:(02)2794-8004		ATPL-125	
RELEASE		02/28/2001	PAIR		SUEDY	UNITS:	SAFETY		SHEET 1 OF 1
NO:	DESCRIPTION	DATE	BY	CHK	APPD	M/M			DRAW
REVISIONS						DATE			<i>Pair</i>
						02/28/01			