



ELECTRICAL CHARACTERISTICS: (FOR C1603 COMPATIBLE)

1. D.C.R. : 10-8=9-7=0.59 OHM MAX 1-3=0.67 OHM MAX 2-4=0.67 OHM MAX.
2. INDUCTANCE : (@10KHZ, 0.1Vrms, 8-9 SHORT) 7-10 = 0.44 mH ±5%
3. LEAKGE INDUCTANCE : (@100KHZ, 0.1Vrms, 8-9, 1-4, 2-3 SHORT) 10-7 = 10uH MAX.
4. TURN RATIO : (@10KHZ, 0.1Vrms, 8-9, 2-3 SHORT) 1-4 : 10-7 = 1±1%
5. HI-POT (@ 1500 VAC, 0.5mA, 1SEC, 2-3,8-9 SHORT) 1-10

						 <b>Atech Technology Co., Ltd.</b> <small>TEL:(02)2794-6667 FAX:(02)2794-8004</small>		TITLE ADSL TRANSFORMER	
								DWG. NO. ATS-454	
RELEASE	06/30/00	FENG		SUEDY	UNITS: M/M	SAFETY		SHEET 1 of 1	
NO. DESCRIPTION	DATE	BY	CHK	APPD	DATE			DRAW <i>Pair</i>	
REVISIONS					06/30/00				