



ELECTRICAL CHARACTERISTICS : <51337R COMPATIBLE>

1. DCR : PIN 7-6 = 0.155 OHM ± 12%
PIN 1-3 = 2-4 = 0.8 OHM ± 12%
PIN 8-5 = 0.195 OHM ± 12%
2. INDUCTANCE (@10KHZ, 0.1Vrms) :
PIN 1-4 (2-3 SHORT) = 171uH ± 5%
3. LEAKAGE INDUCTANCE (@100KHZ, 0.1Vrms) :
PIN 1-4 (W/H 2-3 7-5 8-6 SHORT) = 11uH MAX.
4. INTERWINDING CAP. (@10KHZ, 0.1Vrms) :
PIN 1-8 (2-3 5-7 SHORT) = 50pF MAX.
5. TURN RATIO (@2MHZ, 1Vrms) : PIN 1-4 (2-3 SHORT) : 8-6 (5-7 SHORT) = 2.8 ± 1%
6. HI-POT (@1875VAC, 1mA, 1SEC) : PIN 1-8 (2-3 5-7 SHORT)

						Atech [®] Atech Technology Co. Ltd. TEL:022794-6667 FAX:022794-8004	TITLE	TRANSFORMER
							DWG. NO.	ATS-588A
RELEASE	05/30/2002	DOLLY	CPLIU	SUEDY	UNITS:	SAFETY	SHEET 1 OF 1	
NO.	DESCRIPTION	DATE	BY	CHK	APPD			M/M
REVISIONS						DATE	05/30/02	
							DRAW	Pair