



ELECTRICAL CHARACTERISTICS: (MEET UL 1950, IEC-950)

1. D.C.R. : PIN 1-4 = 4 OHM MAX. 10-7 = 0.7 OHM MAX.
2. INDUCTANCE : (@10KHZ, 0.1Vrms) 1-4 = 1.5mH +/-5%
3. LEAKAGE INDUCTANCE : (@100KHZ, 0.1Vrms)
1-4 (W/H 10-7 SHORT) = 18 uH MAX.
4. Cw (@100KHZ, 0.1Vrms) 1-10 = 35pF MAX.
5. TURN RATIO (@400KHZ, 1Vrms) 1-4 : 10-7 = 1.423 +/-2%
6. LONGITUDINAL BALANCE : AT 100KHZ = 60dB MIN.
7. HI-POT (@1800 VAC, 1mA, 2SEC.) : PIN 1-10

						Atech [®] Atech Technology Co., Ltd. TEL:(02)788-1958 FAX:(02)788-1960	TITLE ADSL TRANSFORMER	
B	DEL. FRAME	12/15 /99	PAIR		SUEDY		DWG. NO. ATS-330	
A	H=12.7MAX	08/31 /99	PAIR		SUEDY			
RELEASE						UNITS: M/M	SAFETY	
NO:	DESCRIPTION	DATE	BY	CHK	APPD	DATE	SHEET 1 OF 1	
REVISIONS						11/23/98	DRAW <i>Pair</i>	